

## Adjustable angle mounting bracketry for 3D LED Flex 25 and 3D LED Flex 40 systems




Standard adjustable mounting brackets:


RAD 3D LED FLEX BRACKET PC

Polycarbonate - black or white finish. IP20 applications.

3D LED Flex 25:



3D LED Flex 40:




Standard IP65 adjustable mounting brackets:


RAD 3D LED FLEX BRACKET AL

Aluminium with powder coat finish (black, white or any RAL colour). IP65 applications.

3D LED Flex 25:



3D LED Flex 40:



### Adjustable angle brackets for 3D LED Flex 25 and 3D LED Flex 40 systems

The 3D LED Flex 25 and 3D LED Flex 40 systems are flexible in 3 dimensions, which allows them to follow curved building contours. Once they have been fixed to the building surface, the adjustable angle brackets allow the modules to then be rotated to any angle around the major axis, so that the light output can be aimed precisely in the desired way

The angle of the modules can be adjusted easily on-site by hand. The friction ball-joint system keeps the modules correctly positioned.

Standard height versions, or a custom height version available


There are IP20 Polycarbonate versions, standard IP65 versions and stainless-steel IP65 versions for more demanding outdoor applications

Taller IP65 adjustable mounting brackets:


RAD 3D LED FLEX BRACKET AL TALL

Aluminium with powder coat finish (black, white or any RAL colour). IP65 applications.

3D LED Flex 25:



3D LED Flex 40:




Custom height adjustable mounting brackets:


RAD 3D LED FLEX BRACKET SS

Stainless steel - powder coat finish (black, white or any RAL colour). More demanding IP65 applications.


3D LED Flex 25:




3D LED Flex 40:




Product code	IP	Height of legs (mm)	Finish
RAD 3D LED FLEX BRACKET PC	20	Stainless steel version only:	Polycarbonate:
RAD 3D LED FLEX BRACKET AL	65	20mm	Black White
RAD 3D LED FLEX BRACKET AL TALL		-increments of 5mm up to-	Aluminium & Stainless steel:
RAD 3D LED FLEX BRACKET SS		100mm	Black White Any RAL colour




Plan view of modules on brackets. The nominal module length for both 3D LED Flex 25 and 40 systems is 100mm with all types of bracket - a strip of 10 modules is 1 Mtr long with each of the bracket types.



Standard IP20 bracket



Standard and tall IP65 brackets



Custom height IP65 bracket