

MR16 Snap Spotlight IP20

Interior LED spotlight optimised to integrate with Soraa Snap MR16 LED lamps

Product description:

Interior spotlight designed to be used in a wide variety of hospitality, gallery, museum, high-end retail and residential applications where the quality and control of light is of high importance

Soraa's MR16 is the only MR16 lamp available which incorporates both Soraa Natural WhiteTM and Soraa Vivd ColorTM technologies, providing the most accurate and rich rendering attainable. Now featuring V+B technology, this line of lamps produces 95+ CRI, 95+ R9, 95+ Rf and 100 Rg. Superior optics design also allows the flexibility of use with Soraa Snap accessories. Single source LED, with the high CBCP and crisp single shadow of a halogen lamp. Soraa HEALTHY™ lamps available, designed with 100% blue-free spectrum technology

Available in 7.5W and 9W power levels. Available in 2700K, 3000K, 4000K, in beam angles of 10°, 25° and 36°

Either remote driver, or remote power supply with integral DC to DC dimmable LV constant current driver housed in the track adapter or surface mount base. 0-10V, DMX or Dali Dimmable


Soraa Magnetic Snap accessories include beam shifting accessories, colour temperature shifting accessories and 40 $^\circ$ honeycomb louvre


Spotlights are rotatable in two axes. The spotlight can be used with Radiant's Micro Track, which is one of the smallest section low voltage tracks available, or a low voltage magnetic track can be used, which allows easy installation and movement of the spotlights on-site. The magnetic track has separate track circuits for low voltage power and dimming ensuring excellent dimming control with all protocols


Satin black, satin white or any RAL colour finish


MR16 Snap LED Spotlight

Interior LED Spotlight - Up to 9 Watts











Up to 700 Lumens per spotlight

Product Code	IP	LED Type	Watts per spotlight	Colour Temp. (K)	CRI	Optics	Mounting type	Snap-on accessories	Finish
MICRO TRACK MR 16 SNAP	20	Soraa Vivid MR16 range	7.5 W 9 W	27=2,700k 30=3,000k 40=4,000k	95	10° 25° 36°	Micro Track Magnetic Track Surface mount base	Honeycomb Beam spreaders: 17°, 25°, 36°, 60°, elliptical beam Flat Top CCT SHIFTER: 1/4, 1/2, 3/4	Powder coat: Black White Any RAL colour

Radiant Architectural Lighting 10 Broadbent Close 20 - 22 Highgate High Street London N6 5JW ENGLAND UK

T: + 44 (0) 20 8348 9003 F: + 44 (0) 20 8348 6478 E: david@radiantlights.co.uk www.radiantlights.co.uk EN 60598 **C€** The information in this document is provided without liability and subject to change without notice

REV 1

Products and literature designed by OAVID MORGAN ASSOCIATES